

Product Name :
Georadar Penetrating Radar

Product Code :
TEST5107RFQLAB-0002



Description :

Georadar Penetrating Radar for Testing Lab Equipment Tender Suppliers India

Technical Specification :

Ground penetrating radar is a versatile GPR system offering various detecting combination for application in highway, roads, tunnel construction, paving, buildings, bridges, water conservancy, municipalities or military. portable high-performance GPR controller compatible with full series antennas. This device is versatile with wide application range, meanwhile automatically recognize antenna type and configure radar parameters. The Windows-system-based acquisition system is stable and reliable which saves both original data and in-field data. The controller accepts most external installed GPS and be able to add the geographic coordinate information to radar data. The digital signal is transmitted between controller and antenna with high anti-interference ability and good signal-to-noise performance.

GPR controller: Single channel controller

Compatible antenna: antennas

Working channel: 1 channel

Storage space: 128G

Display screen: 10.4", 1024x768 pixel resolution, 32 bit color LED

Accept GPS: Serial Port RS232, accepts GPGGA data format

Display mode: False color, gray level, stacking waves and color stacking wave

Power supply: built-in lithium battery

Power consume: 20W

Continue working time: about 3 hours (depend on temperature, antenna type and cable length)

Measurement: Around 314mmx238mmx64mm

Weight: Around 3kg (without battery)
Working temperature: -20?~+50?
Storage temperature: -40?~+60?
Working humidity: Waterproof level: IP65
Data collection
Data format: GER (SRD)
ADC bits: 16 bit
The max scanning speed: 512 scanning/s (sampling points number is 512)
Sampling points number: 256, 512, 1024, 2048, 4096, 8192
Max transmitting frequency: 800kHz
Collecting modes: Time mode, distance mode and point measurement mode
Time-window range: 1~8000ns
Gain range: -10dB~160dB
Number of gain adjustment points: 9 pieces
Real time processing functions: Correction zero deviation, FIR filtering, IIR filtering, background removal, average among ways, data overlying
Exterior installing terminals
Data transmission: USB 3.0
GPS: Serial port (RS232) (GPS device is optional)
Main control: 8-pin aviation socket
GPR controller: Dual channel controller (max. upto 8 channels)
Compatible antenna: antennas
Working channel; 2 channels (equip with laptop)
Power consume: 40W
ADC bits: 16 bit
The max scanning speed: 512 scanning/s (sampling points number is 512)
Sampling points number: 256, 512, 1024, 2048, 4096, 8192
Max transmitting frequency: 800kHz
Collecting modes: Time mode, distance mode and point measurement mode
Time-window range: 1~8000ns
Gain range: -10dB~160dB
Real time processing functions: Correction zero deviation, FIR filtering, IIR filtering, background removal, average among ways, data overlying

We are a leading manufacturers of Georadar Penetrating Radar testing equipment for a range of industries, including materials science testing lab. We offer full range of Georadar Penetrating Radar testing equipment, including Georadar Penetrating Radar testing kit, Georadar Penetrating Radar testing machine, Georadar Penetrating Radar testing tools, Georadar Penetrating Radar test equipment, Georadar Penetrating Radar test machines, Georadar Penetrating Radar for Lab Testing Instruments. We are suppliers of materials testing tools and equipment for the construction industry. Our mission is to provide reliable, accurate, and easy-to-use Georadar Penetrating Radar testing equipment that helps customers build better, safer, and more sustainable infrastructure.



Testing lab instruments India